

# HaloX<sup>®</sup> 100 multi-conduit entry.

Installation housing for a wide range of uses in concrete.

Also for prefabricated cables.

**NEW**



# HaloX® 100 multi-conduit entry.

- 4 M20/M25 combination entries with toolless opening technology
- Multi-conduit entries up to M40 with integrated conduit retention
- Minimal effect on the statics – no cuts to the reinforcement required
- Shape-retaining, loadable, easy to process
- For use with all HaloX® 100 front parts



4 M20/M25 combination entries with toolless opening technology.



Multi-conduit entries up to M40 and cable entries.



Optimal for multimedia applications through multiple conduit entries up to M40.



Integrated conduit retention.

## HaloX® 100 multi-conduit entry



<b>Ceiling exit (CE) Ø</b>	<b>0-100 mm</b>
max. installation depth luminaire / loudspeaker	110 mm
LED wattage max.	20 Watt
Lamp wattage max.	50 Watt
Housing diameter Ø	130 mm
Depth incl. front part	120 mm
Combination entry for M20/M25 conduits	6
Combination entry for M25/M32 conduits	1
Combination entry for M32/M40 conduits	1
Cable entries of up to Ø 16 mm	4
Cable entries of up to Ø 32 mm	1
<b>Art. No.</b>	<b>1281-15</b>
Inner packaging/shipping	- / 10

## One system for all situations



HaloX® for on-site mixed concrete



HaloX® for precast concrete



HaloX® for retrofitting

